

HOL 270








HOL 270 is a compact solution with a redundant uplink for productions where space is limited. Extremely suitable for 'add-on' productions like events, live sports, talk shows on location, etc..



GENERAL


EQUIPMENT

	6 (HD or UHD), unlimited in case of DiPlay
	HD
	HD/ UHD :1
	Sony MVS-3000A
	Yamaha O2R 96

TRUCK DETAILS

 Rigid
7 production workstations

POWER REQUIREMENT

 3 phase 5p CEE 32Amp
3 phase 15KVA

HOL 270



PROCESSING POWER

UP TO 6 CAMERAS UHD/HD

VIDEO

Video Mixer 1	Sony MVS-3000A, 2ME
Panel Video Mixer 1	Sony ICP-3000, 2ME
Multiviewers / Monitors	Axon MV & Sony monitors
Video Mixer 2	n.a.
Panel VideoMixer 2	n.a.
Router	GV 64X64
Controler	GV
Cameras	Cameras & Lenses HD, UHD, Highspeed & Wireless on Request

AUDIO

Audio Mixer	Yamaha O2R 96, 24 faders
Monitoring	Genelec
Devices	Waves server

INTERCOM

Intercom matrix	RTS 24x24
Intercom panels	6 Keypanels
Wireless intercom	Motorola

SERVERS / LSM

Server positions	1x EVS position
Server type	on request , Sony HDCAM/XDCAM, EVS XT 3 & XT VIA, SimplyLive Vibox 8 & 16, Sony PWS 4500

HOL 270



DIMENSIONS & WEIGHT



MAIN TRUCK BR-XR-40

Length	Truck : 8,00m
Height	3,85 m
Weight	12 tons
Width	2,50m
Generator	Onboard 25kVA



TRANSMISSION

Eutelsat ID	HOL 219
Antenna	Vertex SM-LT 2,4 m (13,75 -14,5 GHz)
Amplifier	2x 400 Watt HPA Xicom XTRD-400K (max 74dBW EIRP fase combined)
Encoding/IRD/Modulation	Redundant encoding / IRD / modulation: ATEME, Adtec, Ericsson, Newtec (HD H264/DVBS2)
Sat. Registrations	Eutelsat, SES, Intelsat
Multiplexing	Optional 2+1 / 3+1 output, multiplexing

CONTACT

sales@nl.emglive.com

www.emglive.com